

SEGWAY Drift W1 - PBCDRIFTF1



Damage Protection
The rubber footplate protects and prevents your device from



Slip Resistant Foot Mat
Maximizes your riding comfort by preventing your feet



Unique Design with Innovative Technologies
Smart Management System (SMS) ensures that no battery power is





Silicone Bumpers
RGB LED Lights
45 Mins Battery Range
22-220 lbs (10-100 kg) Payload
10% Hill Grade
IPX6 Splash Proof
Portable

Rating: Not Rated Yet
Price

\$699.00

[Ask a question about this product](#)

Description



Segway Drift W1
Dimensions

Weight
Rider

Machine Parameters

Battery

Mainframe (single wheel)	11.5×6.4×4.8 in (291×162×121 mm)
Unit	12.5×10.6×8.7 in (318×269×219 mm)
Net (single wheel)	Approx. 7.7 lbs (3.5 kg)
Payload	22-220 lbs (10-100 kg)
Recommended Age	6+ years old. See the weight limit
	Approx. 7.5 mph (12 km/h)
Max. Speed	Top speed will vary based on riding style and remaining battery life. Top speed will be reduced when the battery is low.
	45 minutes
Typical Riding Time	10°
Max. Slope	Flat, hard ground free of bumps or obstacles
Traversable Terrain	14-104°F (-10-40°C)
Operating Temperature	-4-122°F (-20-50°C)
Storage Temperature	Mainframe IP54/ Battery pack IPX6
IP Rating	Approx. 180 days/100% power; Approx. 30 days/30% power
Max. Storage Time	Approx. 3 hours
Charge Time (for both mainframes)	22.2 VDC
Nominal Voltage	25.2 VDC
Max. Charging Voltage	32-104°F (0-40°C)
Charging Temperature	44.4 Wh
Nominal Capacity	

Segway Drift W1	Battery Management System	Over-voltage, under-voltage, over-current, short circuit, and over-heating protection. Auto-sleep, auto-balance, and auto-wake.
Motors	Max. torque (single wheel)	6 Nm
	Output Power	37.5 W
	Input Voltage	100-240 VAC
Charger	Output Voltage	25 ± 0.2 VDC
	Output Current	1.5A